

## A-Core Container

# Vertical distance of mobile power box



## Overview

---

The vertical distance between the bottom surface of fixed distribution box and switch box and the ground shall be greater than 1.3m and less than 1.5m; The vertical distance between the bottom of mobile distribution box and switch box and the ground should be greater than 0.6m and less than 1.5m; All distribution boxes and switch boxes must be rainproof and dustproof. How far from a medium-voltage line can a garage be installed?

1 There's a minimum VERTICAL distance of 4 m between the between the highest part of the building and the closest medium-voltage line. 2 No part of a medium-voltage line passes over the building. Example: Adding a garage at a horizontal distance of less than 3 m from medium-voltage lines may be allowed if BOTH these conditions are met:.

How high should a box be installed?

Avoid areas near water or places that are hard to access. The box should be safe from heat, moisture, and physical damage. This helps prevent electrical problems and makes maintenance easier. In homes, the best height for installation is about 1.5 meters from the floor — it's easy to reach and out of children's reach.

How high should a meter box be installed?

Meter boxes must be installed at: Maximum height of 1800mm from ground level to the top of the box - to enable access without ladders or steps. Minimum height of 450mm from ground level to the bottom of the box - to reduce the risk of water entering the box in the event of flooding or fire-fighting activities. Outdoor boxes must not be installed:.

What is the minimum distance between a building and a low-voltage line?

There must be a minimum HORIZONTAL distance of 1.6 m between any part of a building and the closest low-voltage line. This applies to all configurations of low-voltage lines. Example: Adding a storey to a building near a low-voltage line.

Can a meter box be positioned behind a gate or fence?

Meter boxes must not be positioned behind a gate or fence as this could restrict access. The customer's consumer unit must be located so that the conductors from the electricity cut out are no longer than 3m, in order to comply with BS7671 regulations. If the unit exceeds this requirement then suitable switch fused protection must be installed.

How many meter is a high voltage line?

Vertical Distance High voltage lines up to 33KV 3.7 Meter Extra High Voltage 3.7 Meter + Add 0.3 meter for every additional 33KV Horizontal clearance between the conductor and Building High Voltage Up to 11 KV 1.2 Meter 11KV To 33KV 2.0 Meter Extra High Voltage 2.0 Meter + Add 0.3 meter for every additional 33KV

## Vertical distance of mobile power box

---

## Contact Us

---

For catalog requests, pricing, or partnerships, please visit:  
<https://www.a-core.pl>